Holders for Clamping Jaws

Static Holder

SPECIFICATION

Types

- Type **R**: Clamping jaws at right angle to clamping arm
- Type **P**: Clamping jaws parallel to clamping arm

Steel C 45
Chemically nickel plated **NC**

Socket cap screws DIN 912
Centering guide bushings
Steel, blackened







INFORMATION

Holders for clamping jaws GN 869.2 have been designed for use with power clamps GN 865 (see page 1635).
Holders for clamping jaws are equally precisely positioned on the clamping arm as are the clamping jaws GN 872 (see page 1643) on the holders themselves.
Socket cap screws and centering guide bushings are included.

TECHNICAL INFORMATION

- ISO-Fundamental Tolerances (see page A21)





Mounting examples



GN 869.2-R

Description	s -0.2	d1	d2 H8/h6	d3	d4 H8/h6	h	l1	l2	l5	l6	m1	m2	m3	m4	⚖
GN 869.2-32-R-NC	32	M 6	9	M 5	7	10	98.5	30	18.5	8	34	53	17	22	150
GN 869.2-42-R-NC	42	M 8	11	M 6	9	14	140	40	23.5	8.5	51	74.4	23	30	400
GN 869.2-52-R-NC	52	M 10	13	M 8	11	16	168	50	28	12.5	62	88.5	30	37	900
GN 869.2-62-R-NC	62	M 10	13	M 10	13	18	192.5	60	28	12.5	71.5	102	40	44	1030

GN 869.2-P

Description	s -0.2	d1	d2 H8/h6	d3	d4 H8/h6	h	l3	l4	l5	l6	m1	m2	m3	m4	⚖
GN 869.2-32-P-NC	32	M 6	9	M 5	7	10	115.5	13	18.5	8	34	53	17	22	150
GN 869.2-42-P-NC	42	M 8	11	M 6	9	14	163	17	23.5	8.5	51	74.4	23	30	370
GN 869.2-52-P-NC	52	M 10	13	M 8	11	16	198	20	28	12.5	62	88.5	30	37	720
GN 869.2-62-P-NC	62	M 10	13	M 10	13	18	232.5	20	28	12.5	71.5	102	40	44	770

10/2021
ELESA and GANTER models all rights reserved in accordance with the law.
Always mention the source when reproducing our drawings.