



- 2 Type**
- ST** with fixed Steel pin
 - MS** with fixed Brass pin
 - STL** with loose Steel pin
 - STS** with fixed Steel pin and lubricating nipple

1

Length I	Type ST Type MS	Type STL Type STS	d ₁	d ₂ Pin	s ₁	s ₂
40	-	-	8	5	10	2
50	-	-	8	5	10	2
60	-	-	10	6	12	2
80	-	80	13	8	15,5	2
100	-	100	16	10	20	3
120	-	120	16	11	20	3
135	-	135	18	12	23	3
150	-	150	20	13	25,5	3
180	-	180	20	14	25,5	3
200	-	200	23	16	28,5	3

Specification

- Steel, blank
- Pin
 - Type ST / STS / STL
Steel, blank
 - Type MS
Brass, turned, blank
- Washer
Brass
- Lubricating nipple DIN 71412-D
Steel, zinc plated
- RoHS compliant

Information

Hinges GN 128 are produced from drawn weldable profiled steel extrusions.

Types ST, STS and MS feature a hinge pin fixed in the lower half of hinge. Type STL with loose steel pin allows the easy installation when attaching several hinges in parallel or if the door is very heavy.

The upper half of Type STS hinge has an additional lubricating nipple DIN 71412-D which allows the hinges to be lubricated without dismantling the hinges.

How to order	1 Length I
	2 Type

GN 128-80-ST