



d₁ *	l₁					d₂	e ≈	k₁ -1	k₂	l₂ max.	s	Nominal adhesive forces in N
M 6	12	16	20	25	30	10	11	4	3,2	3	10	25
M 8	16	20	25	30	40	13	14,4	5,3	4	3,7	13	50
M 10	20	25	30	40	50	17	17,8	6,4	5	4,5	17	75
M 12	25	30	40	50	60	19	20	7,5	6	5,2	19	110
M 16	30	40	50	60	80	24	26,8	10	8	6	24	145

*thread: nut mobility

Specification

- Screw Steel
 - Tensile strength class 5.8 (500 N/mm²)
 - zinc plated, blue passivated
- Hexagon nut Steel
 - Tensile strength class 04 (400 N/mm²)
 - zinc plated, blue passivated
- Material of the magnet
 - NdFeB
 - Neodymium, iron, boron
 - temperature resistant up to 80 °C
- RoHS compliant

3

Information

Setting bolts GN 251.6 with retaining magnets are a shielded magnetic system.

Suitable e.g. as workpiece stop, with the magnet holding the workpiece in place.

The lock nut (included) can be used to secure the stop screw after positioning.

see also...

- More information to retaining magnets → Page 1094
- Setting bolts GN 251 (without magnet) → Page 584

ND

How to order

GN251.6-M6-12-ND

1	d₁
2	l₁
3	Material of the magnet