



2.1
2.2
2.3
2.4

d ₁	d ₂	l ₁			d ₃	l ₂	l ₃	l ₄ Adjustable range	l ₅	l ₆	l ₇	A/F ₁	A/F ₂	Static load in kN (see Information)	
60	M 16	125	150	175	200	24	45	13	32	4	16	45	20	12	27
80	M 16	128	153	178	203	24	45	13	32	5	18	45	20	12	24
80	M 20	152	177	202	252	30	56	16	40	5	18	56	24	16	24
80	M 24	176	226	276	-	35	67	19	48	5	18	67	30	20	24
100	M 16	130	155	180	205	24	45	13	32	6	20	45	20	12	21
100	M 20	155	180	205	255	30	56	16	40	6	20	56	24	16	21
100	M 24	179	229	279	-	35	67	19	48	6	20	67	30	20	21

2.5
2.6

Specification

- **GN 341.1**
Rubber underlay (NBR), black vulcanized, 85 ... 90 Shore
 - **GN 341.2**
Rubber underlay (NBR), white vulcanized, 85 ... 90 Shore
- This information applies to both standards:
- Foot
Stainless Steel AISI 304
- matt shot-blasted
- polished
 - Screw / adjustable sleeve
Stainless Steel AISI 303
 - Hexagon nut ISO 4032
Stainless Steel AISI 304
 - Fixing screw
Stainless Steel A2, loctited
 - *Stainless Steel characteristics* → Page 1144
 - *Elastomer characteristics* → Page 1140
 - **RoHS compliant**

MT
PL

Information

Stainless Steel-Levelling feet for application in hygiene environment GN 341.1 / GN 341.2 have been designed to meet requirements in the food industry. With the convex shaped bolt head seat on the Stainless Steel foot, the formation of deposits is greatly reduced and the cleaning is simplified.

The rubber underlay is **vulcanized** into the Stainless Steel foot. The adjustable sleeve is shrouding the thread over its adjustable length and sharp edges and corners have been to a large extent avoided.

Stainless Steel-Levelling feet GN 341.1 / GN 341.2 obtained the EQUIPMENT ACCEPTANCE CERTIFICATE of USDA (US-Department of Agriculture).

The load figures specified in the table above are based on a series of tests whereby a vertical load in relation to the horizontal plane of the foot is applied. If the above figures are exceeded, a permanent deformation of the Stainless Steel foot can occur.

2.7
2.8
2.9

How to order		1	d ₁
		2	d ₂
		3	l ₁
		4	Finish
GN341.2-60-M16-125-PL			