



3 Type

- OS neutral
- ES with DIN re-fill symbol
- AS with DIN drain symbol

4 Identification

- 1 without vent drilling
- 2 with vent drilling

1	2				d₃ Vent drilling	d₄	l₁	l₂	t	s	e ≈
19	G 1/4	M 14 x 1,5	-	-	2	M 5	15,5	8	8	15	17,3
22	G 3/8	M 16 x 1,5	-	-	2	M 5	15,5	8	8	18	20,8
26	G 1/2	M 20 x 1,5	-	-	2	M 5	16	8,5	8	21	24,3
32	G 3/4	M 26 x 1,5	M 27 x 1,5	-	2	M 5	17	9	8	27	31,2
40	G 1	M 33 x 1,5	-	-	2	M 5	19,5	11	8	32	37
50	G 1 1/4	M 40 x 1,5	M 42 x 1,5	M 42 x 2	2	M 5	21	12	8	41	47,3
60	G 1 1/2	-	-	-	2	M 5	22	13	8	50	57,7

Specification

- Aluminium
 - fine turned
 - Symbols laser engraved
- **GN 741**
 - temperature resistant up to **100 °C**
 - Sealing ring rubber NBR (Perbunan)
- **GN 742**
 - temperature resistant up to **180 °C**
 - Sealing ring rubber FPM (Viton®)
 - Identification by not black finish of seal
- *Elastomer characteristics* → Page 1140

On request

- with dipstick

Information

Threaded plugs GN 741 / GN 742 are fitted with outside diameter d₁ to suit screw holes with BSP threads to DIN 3852.

The sealing ring is bedded into a undercut groove which prevents it from dropping out and at the same time stops it from being extruded when tightening the cap.

see also...

- *Threaded plugs GN 745 (Plastic)* → Page 915
- *Threaded plugs with catch GN 441 / GN 442* → Page 919

Threaded plug	1 d ₁
1 2 3 4	2 d ₂
GN 741-26-G1/2-OS-1	3 Type
	4 Identification

Threaded plug	1 d ₁
1 2 3 4	2 d ₂
GN 742-32-M26x1,5-ES-2	3 Type
	4 Identification