



d₁	Length l ±0,25	d₂	d₃	h	r	t min.
8	55	M 4	12	35	10	8
8	64	M 4	12	35	10	8
8	88	M 4	12	35	10	8
8	96	M 4	12	35	10	8
8	100	M 4	12	35	10	8
8	120	M 4	12	35	10	8
8	128	M 4	12	35	10	8
10	88	M 5	15	43	12	12
10	100	M 5	15	43	12	12
10	120	M 5	15	43	12	12
10	180	M 5	15	43	12	12
10	200	M 5	15	43	12	12
10	235	M 5	15	43	12	12

Specification

- GN 425**
Steel
 - plastic coated
 - red, RAL 3000, textured finish
 - black, RAL 9005, textured finish
 - chrome plated
 - blackened
- Washers
Zinc die casting, nickel plated
- GN 425.6**
Aluminium
 - plastic coated
 - black, RAL 9005, textured finish
 - silver, RAL 9006, textured finish
 - anodized, natural colour
- Washers
Stainless Steel AISI 303
- Load rating information → Page 1149*
- RoHS compliant



- RT
- SW
- CR
- BT

Information

Cabinet „U“ handles GN 425 / GN 425.6 are supplied with two location discs. They guarantee a perfect location even with large holes in the cabinet. The discs are loosely enclosed.

The chrome-plated design is only conditionally suitable for outdoor use. The stainless steel design version should be given preference.

The manufacturing process (bending) allows the production of **special lengths** in relatively small quantities.

see also...

- Stainless Steel-Cabinet „U“ handles GN 425 → Page 82

Cabinet „U“ handle GN 425-10-120-CR	1	d ₁
	2	Length l
	3	Finish

Cabinet „U“ handle GN 425.6-8-88-EL	1	d ₁
	2	Length l
	3	Finish