

Rostfrei
 Inch sizes available
 Inox Stainless Steel

4 Type

- OS** without plastic cap
- KR** with plastic cap, non-gliding
- GV** with rubber, vulcanized

1 2 3

d ₁	d ₂	l ₁					d ₃	l ₂	l ₃	l ₄	l ₅	s ₁	s ₂	s ₃	A/F ₁	A/F ₂	A/F ₃	Static load in kN (see information)	
																		GN 440	GN 440.5
40	M 8	40	50	63	-	-	43	10,5	-	5	5,5	2	1,5	3,5	17	-	-	7	8
40	M 10	50	60	80	100	-	43	10,5	-	5	5,5	2	1,5	3,5	17	-	-	7	12
40	M 12	60	80	100	125	-	43	10,5	-	5	5,5	2	1,5	3,5	17	-	-	7	12
40	M 16	75	100	125	150	200	43	-	16,5	5	5,5	2	1,5	3,5	-	12	8	7	12
50	M 8	40	50	63	-	-	54	11	-	6	6,5	2,5	2	4	17	-	-	8	8
50	M 10	50	60	80	100	-	54	11	-	6	6,5	2,5	2	4	17	-	-	8	14
50	M 12	60	80	100	125	-	54	11	-	6	6,5	2,5	2	4	17	-	-	8	14
50	M 16	75	100	125	150	200	54	-	17	6	6,5	2,5	2	4	-	12	8	8	14
60	M 8	40	50	63	-	-	64	11	-	6	7	2,5	2	4,5	17	-	-	8	8
60	M 10	50	60	80	100	-	64	11	-	6	7	2,5	2	4,5	17	-	-	10	14
60	M 12	60	80	100	125	-	64	11	-	6	7	2,5	2	4,5	17	-	-	10	16
60	M 16	75	100	125	150	200	64	-	17	6	7	2,5	2	4,5	-	12	8	10	16
80	M 8	40	50	63	-	-	84	11	-	7	8	3	2	5	17	-	-	8	8
80	M 10	50	60	80	100	-	84	11	-	7	8	3	2	5	17	-	-	10	14
80	M 12	60	80	100	125	-	84	11	-	7	8	3	2	5	17	-	-	12	20
80	M 16	75	100	125	150	200	84	-	17	7	8	3	2	5	-	12	8	12	20
80	M 20	75	100	125	150	200	84	-	18	7	8	3	2	5	-	15	10	16	20
80	M 24	100	125	150	200	-	84	-	20	7	8	3	2	5	-	19	12	16	22



2.1
2.2
2.3
2.4
2.5

Specification

- **GN 440**
Steel zinc plated, blue passivated
 - Foot for type GV
 - Stainless Steel AISI 304
 - Screw
 - Tensile strength class 5.8 (500/mm²)
- **GN 440.5**
Stainless Steel
 - Foot / Hexagon nut AISI 304
 - Screw AISI 303

This information applies to both standards:

- Fixing screw
Stainless Steel A2, loctited
- Plastic cap
 - Elastomer (TPE)
 - 73 shore, black
- Rubber underlay (NBR)
 - 70±5 shore, black
 - vulcanized
- *Elastomer characteristics* → Page 1140
- *Stainless Steel characteristics* → Page 1144
- **RoHS compliant**

Information

Levelling feet GN 440 / GN 440.5 are an easy and very reasonably priced foot design variant.

The static load capacity in the table above are based on a series of tests whereby a vertical load in relation to the horizontal plane of the foot is applied. For the values given in the table, the strain relief may result in minor deformations of the foot.


The details relating to the load bearing capacity are non-binding recommended values and rule out any liability. They constitute no general warranty of quality and condition. The user must determine from case to case whether a product is suitable for the intended use.

see also...

- *Levelling feet GN 440.1 / GN 440.6 (with fixing lug)* → Page 836
- *Levelling feet GN 440 / GN 440.5 (with internal thread)* → Page 830

2.6
2.7
2.8
2.9

Steel-Levelling feet		1	d ₁
 GN 440-50-M12-80-OS		2	d ₂
		3	l ₁
		4	Type

Stainless Steel-Levelling feet		1	d ₁
 GN 440.5-80-M12-60-KR		2	d ₂
		3	l ₁
		4	Type