

**3 Type**

- OS** without plastic cap, non-gliding
- KR** with plastic cap, non-gliding
- GV** with rubber, vulcanized

**1**

**2**

d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	l <sub>4</sub>	r	s <sub>1</sub>	s <sub>2</sub>	s <sub>3</sub>	A/F	t min.	Static load in kN	
													GN 440.1	GN 440.6
50	M 8	13	25	6	6,5	45	15	2,5	2	4	14	8	8	8
50	M 10	13	28	6	6,5	45	15	2,5	2	4	14	10	8	14
50	M 12	13	32	6	6,5	45	15	2,5	2	4	17	12	8	14
50	M 16	13	37	6	6,5	45	15	2,5	2	4	22	16	8	14
60	M 8	13	25	6	7	50	15	2,5	2	4,5	14	8	8	8
60	M 10	13	28	6	7	50	15	2,5	2	4,5	14	10	10	14
60	M 12	13	32	6	7	50	15	2,5	2	4,5	17	12	10	16
60	M 16	13	37	6	7	50	15	2,5	2	4,5	22	16	10	16
80	M 8	13	26	7	8	70	15	3	2	5	14	8	8	8
80	M 10	13	29	7	8	70	15	3	2	5	14	10	10	14
80	M 12	13	32	7	8	70	15	3	2	5	17	12	12	20
80	M 16	13	38	7	8	70	15	3	2	5	22	16	12	20
80	M 20	13	45	7	8	70	15	3	2	5	27	20	16	20


 2.1  
2.2  
2.3  
2.4  
**2.5**

### Specification

- **GN 440.1**  
Steel
  - zinc plated, blue passivated
  - Foot for type GV  
Stainless Steel AISI 304
  - Threaded bush  
Tensile strength class 5.8 (500 N/mm<sup>2</sup>)
- **GN 440.6**  
Stainless Steel
  - Foot AISI 304
  - Threaded bush AISI 303

This information applies to both standards:

- Fixing screw  
Stainless Steel A2, loctited
- Plastic cap  
Elastomer (TPE)  
73 Shore, black
- Rubber underlay (NBR)  
70±5 Shore, black  
vulcanized
- *Elastomer characteristics* → Page 1140
- *Stainless Steel characteristics* → Page 1144
- **RoHS compliant**

### Information

Levelling feet GN 440.1 / GN 440.6 are an easy and very reasonably priced foot design variant.



The static load bearing capacity given in the table rests on a test series in which the load has been applied perpendicular to the plate. For the values given in the table, the strain relief may result in minor deformations of the foot. The details relating to the load bearing capacity are non-binding recommended values and rule out any liability.

They constitute no general warranty of quality and condition. The user must determine from case to case whether a product is suitable for the intended use.

see also...

- *Levelling feet GN 440* → Page 830
- *Stainless Steel-Levelling feet GN 440.5* → Page 830

 2.6  
2.7  
2.8  
2.9  
🔧

Steel-Levelling foot	1	d <sub>1</sub>
  	2	d <sub>2</sub>
<b>GN 440.1-60-M16-GV</b>	3	Type

Stainless Steel-Levelling foot	1	d <sub>1</sub>
  	2	d <sub>2</sub>
<b>GN 440.6-80-M16-KR</b>	3	Type