



ROSTFREI
Inox
Stainless
Steel

- 4 Type**
- MS** Brass pivot
 - KU** Plastic pivot (Polyacetal POM)
 - ZK** spherical pivot

1 2 3

d ₁	d ₂	l ₁				d ₃	d ₄ Brass pivot	d ₅ Plastic pivot	d ₆ Spherical pivot	h ₁	h ₂	l ₂ Brass pivot	l ₃ Plastic pivot	l ₄ ≈ Spherical pivot
34	M 6	15	20	25	30	16	4	3,5	4,5 ±0,03	21	10,5	1	1,3	5,1
42	M 8	20	25	30	40	19	6	5	6,1 ±0,05	26	13	1,5	1,6	6,2
53	M 10	25	30	40	50	24	8	6,5	7,8 ±0,05	32	16	2	1,9	7,3

Specification

- Plastic Technopolymer (Polyamide PA)
 - glasfibre reinforced
 - temperature resistant up to 130 °C
 - black, matt
- Threaded bolt
Stainless Steel AISI 304
- Cover cap plastic
light grey, matt
- Plastic characteristics → Page 1141
- Stainless Steel characteristics → Page 1144
- RoHS compliant

Information

Knurled screws GN 7336.5, type MS / KU with brass or plastic pivots are used when pressure dents or damage must be avoided.

Knurled screws GN 7336.5, type ZK feature a spherical pivot whose Ø d₆ is smaller than the core Ø of the thread. The version with spherical pivot is suitable for holding GN 631 / GN 631.5 thrust pads, which must be ordered separately.

These knurled screws GN 7336.5 distinguish an attractive design in combination with closed shape (no recess on the underside of the handles).

see also...

- Thrust pads GN 631 / GN 631.5 → Page 597
- Stainless Steel-Hexagon screws GN 933.5 → Page 527 (with brass / plastic / spherical pivot)

How to order	1 d ₁
	2 d ₂
	3 l ₁
GN 7336.5-42-M8-25-MS	4 Type