



1		2		3														
l ₁	d ₁			l ₂		d ₃	d ₄	h ₁	h ₂	h ₃	h ₄	Stroke						
30	M 3	-		6	8	10	12	16	-	-	-	10	13	26,5	4	31	3,5	
30	M 4	-		12	16	20	25	32	-	-	-	10	13	26,5	4	31	3,5	
30	M 5	M 6		12	16	20	25	32	40	50	-	10	13	26,5	4	31	3,5	
45	M 4	-		12	16	20	25	32	-	-	-	10	13	26,5	4	35	3,5	
45	M 5	M 6		12	16	20	25	32	40	50	-	10	13	26,5	4	35	3,5	
63	M 6	M 8		12	16	20	25	32	40	50	63	13,5	17,5	32,5	6,5	45	4	
63	M 10	-		20	25	32	40	50	63	80	-	13,5	17,5	32,5	6,5	45	4	
78	M 8	M 10		16	20	25	32	40	50	63	80	16	21	37,5	8	55	4	
78	M 12	-		25	32	40	50	63	80	-	-	16	21	37,5	8	55	4	

Specification

- Handle
Zinc die casting
- plastic coated black, RAL 9005 textured finish ● SW
- Push button
Plastic black, RAL 9005 orange, RAL 2004 grey, RAL 7035 ● S ● O ● G
- Threaded insert
Steel, blackened
- Pin for push button
Stainless Steel
- RoHS compliant

On request

- Handle in colours of GN 300

Information

Adjustable hand levers GN 303 are ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

The push button is a design element that offers an easy disengagement. Its use is limited to applications where dismantling of the lever for installation is not required.

see also...

- Adjustable hand levers GN 303.1 (insert Stainless Steel) → Page 205

How to order

1	l ₁
2	d ₁
3	l ₂
4	Handle colour
5	Push button colour

GN 303-63-M8-25-SW-G