



Inch sizes available

¹ l ₁	² d ₁ Thread			² d ₂ H7 Bore		d ₃	d ₄	h ₁	h ₂	h ₃	h ₄ Stroke	t min.
30	M 3	-	-	-	-	10	13	24,5	4	31	3,5	7
30	M 4	M 5	M 6	B 5	B 6	10	13	24,5	4	31	3,5	9
45	M 4	M 5	M 6	B 5	B 6	10	13	24,5	4	35	3,5	9
63	M 6	M 8	-	B 8	-	13,5	17,5	31	6,5	45	4	11
78	M 8	M 10	-	B 8	B 10	16	21	36	8	55	4	14
92	M 10	M 12	-	B 12	-	19	24	43	11	65	4	17
108	M 12	M 14	M 16	B 12	B 16	23	30	50,5	12	76	5	22

Specification

- Handle
Zinc die casting
- plastic coated
black, RAL 9005, textured finish
black, RAL 9011, silk finish
orange, RAL 2004, textured finish
red, RAL 3000, textured finish
silver, RAL 9006, textured finish
- chrome-plated
- uncoated
slide grinded
- Threaded insert and retaining screw
Steel (5.8), blackened
- RoHS compliant

- SW
- SZ
- OS
- RS
- SR
- CR
- RH

Information

Adjustable hand levers GN 300 are ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

Pulling the lever, disengages the serrations and allowing it to be swivelled to the ideal clamping position. On releasing the lever the serrations automatically re-engage.

see also...

- Adjustable hand levers GN 300.1 (insert Stainless Steel) → Page 198
- Adjustable hand levers GN 300.5 (Stainless Steel) → Page 200
- Adjustable hand levers GN 302 (straight handle) → Page 210

How to order	1 l ₁
¹ ² ³	2 d ₁ (d ₂)
GN 300-92-M12-SR	3 Colour (Finish)