



<b>1</b> s ∇ Linear actuator	<b>2</b> d <sub>1</sub> f7	d <sub>2</sub>	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	for position indicator
30	8	14	40	20	21,5	35	15	12	GN 954
40	12	20	50	25	28,5	39	16	12	GN 953
50	12	20	60	30	61,5	39	17	12	GN 953

**Specification**

- Adaptor shaft  
Steel  
blackened
- Torque support  
Aluminum  
blank, ground
- **RoHS compliant**

**Accessory**

- Position indicators and handwheels have to be ordered separately.

**Information**

With the installation kit GN 296 the square linear actuator can be fitted with a digital position indicator.

An installation kit comprises an adaptor shaft and a torque support.

A retrofit is possible. The handwheel is removed, the kit is mounted and the handwheel is refitted.

As a rule a counter is chosen which is matched to the pitch of the spindle with trapezoidal thread so the indicator after one complete revolution accords to the pitch of the spindle.

see also...

- Position indicators GN 953 → Main catalogue page 388
- Position indicators GN 954 → Main catalogue page 390
- Square linear actuators GN 291.1 → Main catalogue page 1056

<b>How to order</b>	<b>1</b> s ∇
	<b>2</b> d <sub>1</sub>

**GN 296-30-8**