


ROSTFREI Rostfrei  
Inox  
Stainless  
Steel

**3 Type**

**C** Fixing from the back side



| 1              |    | 2              |         | b  | d <sub>1</sub> | d <sub>2</sub><br>Pin | h <sub>1</sub> | h <sub>2</sub> | l <sub>3</sub> | l <sub>4</sub><br>max. | l <sub>5</sub> | l <sub>6</sub><br>max. | l <sub>7</sub> | m <sub>1</sub> | m <sub>2</sub> | s  | t  |
|----------------|----|----------------|---------|----|----------------|-----------------------|----------------|----------------|----------------|------------------------|----------------|------------------------|----------------|----------------|----------------|----|----|
| l <sub>1</sub> | ST | l <sub>2</sub> | NI / A4 |    |                |                       |                |                |                |                        |                |                        |                |                |                |    |    |
| 45             | 45 | 40             | 40      | 13 | M 6            | 6                     | 13             | 13,5           | 18             | 6                      | 11             | 5                      | 10             | 30             | 28,2           | 12 | 9  |
| 50             | 50 | 51             | 51      | 18 | M 8            | 8                     | 18             | 18             | 26             | 8                      | 14             | 8                      | 14             | 29             | 35             | 16 | 11 |
| 53             | -  | 40             | -       | 13 | M 6            | 6                     | 13             | 13,5           | 26             | 6                      | 11             | 5                      | 10             | 38             | 28,2           | 12 | 9  |
| 61             | -  | 51             | -       | 18 | M 8            | 8                     | 18             | 18             | 26             | 6                      | 14             | 8                      | 14             | 40             | 35             | 16 | 11 |

**Specification**

- Hinge  
Steel  
zinc plated, blue passivated
- Pin  
Brass, nickel plated
- Washer  
Brass, nickel plated
- Hexagon nut ISO 4032  
Steel zinc plated, blue passivated
- Serrated washer DIN 6797  
for securing screws  
Steel zinc plated, blue passivated

**4**

**Information**

Hinges GN 129.2 are used for doors which are flush with the frame on the outside. Once assembled, they cannot be unhinged.

**ST**

With the fixing from the inside, they are especially suitable for doors and trap doors which must not be detachable from the outside as an anti-tamper device.

see also...

- Hinges GN 129.3 → New products
- Hinges GN 129 → Main catalogue page 893

- Hinge body, pin, washer
  - Stainless Steel AISI 303 **NI**
  - Stainless Steel AISI 316 **A4**
  - Hexagon nut ISO 4032  
Stainless Steel AISI 304
  - Serrated washer DIN 6797  
for securing screws  
Stainless Steel AISI 304

• Stainless Steel characteristics  
→ Main catalogue page 1144

• RoHS compliant

|              |   |                |
|--------------|---|----------------|
| How to order | 1 | l <sub>1</sub> |
|              | 2 | l <sub>2</sub> |
|              | 3 | Type           |
|              | 4 | Material       |

1 2 3 4  
**GN 129.2-53-40-C-ST**