



Installation example



Rostfrei ROESTFREI **Inox**
Stainless
Steel

2 Type

D consisting of three parts

1

s Square	b	d ₁	d ₂ Pin	h	l ₁	l ₂	l ₃	l ₄ max.	m
12	15	M 6	6	39,2	10	5	14	9	27,2
16	20	M 8	8	49	14	8	22	16	33

Specification

- Hinge body, pin, washer
 - Stainless Steel AISI 303
 - Stainless Steel AISI 316
- Hexagon nut ISO 4032
Stainless Steel AISI 304
- Serrated washer DIN 6797
for securing screws
Stainless Steel AISI 304
- Stainless Steel characteristics
→ *Main catalogue page 1144*
- RoHS compliant

3

Information

Stainless Steel-Hinges GN 129.5 are used for doors which are flush with the frame on the outside. Once assembled, they cannot be unhinged.

With the fixing from the inside, they are especially suitable for doors and trap doors which must not be detachable from the outside as an anti-tamper device.

see also...

- Hinges GN 129 (Steel) → *Main catalogue page 996*
- Hinges GN 129.2 (Steel / Stainless Steel) → *New products*
- Hinges GN 129.3 (Steel) → *New products*

How to order

GN 129.5-16-D-A4

1	s
2	Type
3	Material