


2 Type

- A without rest position (lifting ring)
- B without rest position (Knob)



d ₁ Plunger h ₁₁ Bore $\begin{smallmatrix} +0,03 \\ -0,08 \end{smallmatrix}$	d ₂	d ₃	b ₁	b ₂	b ₃	b ₄ -0,2	h ₁	h ₂	k ₁ ±0,05	k ₂	k ₃	k ₄	l ₁	l ₂ ±0,5	Spring load in N ≈	
															initial	end
4	12	14	22	16,5	6	3,3	7	4	14	4	8	4,5	30,5	4	3	12
5	16	18	28	22	8	4,3	9,5	4,5	18	5	10	7	40	5	5	24
6	18	24	32	27,5	10	5,4	10,5	5	21	5,5	12	10	49	6	5	21
8	21	30	34	33	12	5,4	12,5	6	23	5,5	12	15,5	59	8	6	22

Specification

- Guide
Zinc die casting
plastic coated
black, textured finish
- Plunger
Stainless Steel AISI 303
- Spring
Stainless Steel AISI 301
- Lifting ring
Stainless Steel AISI 301
- Knob
Plastic (Polyamide PA)
- black, matt
- not removable
- ISO-Fundamental Tolerances → Page 1132
- Stainless Steel characteristics → Page 1144
- Plastic characteristics → Page 1141
- RoHS compliant

Information

The screwing range of indexing plungers GN 417 is chosen in such a way that washers ISO 7092 can be used.

see also...

- Range of indexing plungers → Page 402
- Positioning bushings GN 412.2 → Page 454

How to order

GN417-6-B

1 d₁

2 Type