



ROSLANDTAL 100
Rost frei
Inox
Stainless
Steel

3 Type

- A** Mounting from the back (threaded blind bore)
- B** Mounting from the operator's side

d₁	l₁ ±0,5 Type A	±0,3 Type B Threaded bore for mounting stud	d₂	d₃	h	l₂	r ≈	t₁	t₂
20	200	200	M 8	-	68	20	22	15	-
20	250	250	M 8	-	68	20	22	15	-
20	300	300	M 8	-	68	20	22	15	-
20	350	350	M 8	-	68	20	22	15	-
28	250	250	M 10	32	90	20	32	-	17
28	300	300	M 10	32	90	20	32	-	17
28	350	350	M 10	32	90	20	32	-	17
28	400	400	M 10	32	90	20	32	-	17

Specification

- **Stainless Steel**
d₁ = 20: Solid material
d₁ = 28: Tube-Ø 28 x 2
- AISI 304
- matt shot-blasted
- **Threaded bush / Mounting stud**
Stainless Steel AISI 303
- **Grub screw (Type B)**
d₁ = 20: DIN 914-M5-6-NI
d₁ = 28: DIN 914-M6-8-NI
- *Stainless Steel characteristics → Page 1144*
- *Load rating information → Page 1151*
- **RoHS compliant**

Information

Stainless Steel-Cabinet „U“ handles GN 426.5 can be mounted from the back (type A) as well as from the operator's side (type B). In this case the stud is first screwed in from the machine side and then the handle is pushed on and secured with the grub screw.

Both mounting methods allow the mounting of a pair of handles in opposite position. This method could be used e.g. on doors (double handle). In general, a mounting stud with special length l₂ might be required.

The manufacturing process (bending) allows the production of **special lengths** in relatively small quantities.

see also...

- *Cabinet „U“ handles GN 426 (Aluminium) → Page 92*
- *Stainless Steel-Tubular handles GN 666.5 / GN 666.7 → Page 112*

How to order	1 d ₁
GN426.5-28-400-A	2 l ₁ (l ₂)
	3 Type

1.1
1.2
1.3
1.4
1.5
1.6
1.7
1.8
1.9