



Rost frei Inox
Stainless
Steel

- 4 Type**
- KS** with plastic cap, gliding
 - KR** with plastic cap, non-gliding

1 d ₁	2 d ₂	3 l ₁		l ₂ ≈		l ₃ ≈		l ₄ Type KS		Type KR	A/F
29	M 6	30	45	8	5	1	1	0,4	3		
29	M 8	35	55	8	5	1	1	0,4	4		
36	M 8	40	65	9	6	1	1	0,5	4		
36	M 10	45	70	9	6	1	1	0,5	5		

Specification

- Steel **ST**
 - Tensile strength class 5.8 (500 N/mm²)
 - zinc plated, blue passivated
 - Hexagon nut ISO 4035
 - Steel zinc plated, blue passivated
- Stainless Steel **NI**
 - AISI 303
 - Hexagon nut ISO 4035
 - Stainless Steel AISI 304
- Plastic caps:
 - Type KS
Technopolymer (Polyacetal POM)
white (natural colour) RAL 9001
 - Type KR
Elastomer (TPE)
73 shore A ≈
black

- Hexagon nut ISO 4035
Steel zinc plated, blue passivated
- *Elastomer characteristics* → Page 330
- *Plastic characteristics* → Page 331
- *Stainless Steel characteristics* → Page 334
- **RoHS compliant**

Information

Levelling feet GN 339 are used for applications in cases where no jointed link is required between foot and adjusting screw. For this reason they offer the advantage of reduced height. The gliding and/or the non-gliding protective cap is safely fixed in the foot.

see also...

- *Discs with cover cap (as simple feet) GN 338*
→ Main Catalogue Page 544

How to order

GN339-36-M10-45-KR-ST

1	d₁
2	d₂
3	l₁
4	Type
5	Steel