




Countersunk for socket cap screw DIN 912



Adjustable clamping lever GN 511




Application example



Retaining magnet GN 51.6



d_1 Bore B for shaft tol. h11	k	d_2 for screw	l_1	l_2	m	s Square V	Clamping lever for d_2 
B 8	14	M 4	31,5	10	22	-	GN 511-M4-20
B 10	16	M 5	38	10,5	27	8	GN 511-M5-25
B 12	16	M 5	38	10,5	27	10	GN 511-M5-25
B 15	20	M 6	45	14	32	12	GN 511-M6-25
B 16	20	M 6	45	14	32	-	GN 511-M6-25
B 20	25	M 6	50	14	36	16	GN 511-M6-32

Specification

- Aluminium
 - matt, slide ground **MT**
 - anodized, black **ELS**
- Adjustable clamping levers GN 511
 - Zinc die casting
 - Inserts / Distance bushings
Stainless Steel AISI 303 → Page 1086
- Stainless Steel characteristics → Page 1144
- RoHS-compliant



Information

The clamp mountings GN 477 have no thread. Fixing or clamping is made via two threads on the attachment side.

The bore distance m of the clamp mountings GN 477 is matched with the foot clamp mountings GN 473 and the flanged bolts GN 480 as well as retaining magnets GN 51.6.

see also...

- Flanged bolts GN 480 → Page 1084
- Retaining rods / tubes GN 480.1 → Page 1085

How to order

GN477-B12-MT

1 d_1

2 Finish

2.1
2.2
2.3
2.4
2.5
2.6
2.7
2.8
2.9