

Range extended!




Rostfrei  
Inox  
Stainless  
Steel


**1** Type

Operation


- RG** with knurled knob in plastic (GN 7336)
- KG** with wrench in plastic
- HG** with lever in plastic
- SG** with St. Steel-Star knob
- KGN** with St. Steel-Wrench
- HGN** with St. Steel-Lever




Type KGN




Type HGN



Type RG



Type KG



Type HG

**2**

Latch distance **A**

6	10	14	18	20	22	24	26	28	30	34	38	40	50
---	----	----	----	----	----	----	----	----	----	----	----	----	----

**Specification**

- Lock housing  
Stainless Steel  
AISI 303
- Latch  
Stainless Steel AISI 304
- Star knobs (Type SG)  
Stainless Steel AISI 304  
- Sheet metal, drawn  
- Hub, welded
- Operating handles (Type KGN, HGN)  
Stainless Steel AISI CF-8
- Operating handles (Type RG, KG, HG)  
Plastic (Polyamide PA)  
black, matt
- Protection class IP 65
- *Stainless Steel characteristics* → Page 334
- **RoHS compliant**

**3**

**Information**

Latches GN 115 lock by a turning operation limited to 90° which moves the locking behind the door frame. The bevels of the latch ease the closing of the door.

Latches with different cranks cover a range A from 6 to 50 mm.

The operating bolt is fitted with an O-ring for sealing.

Stainless Steel-Latches GN 115 are supplied with loosely enclosed locking.

see also...

- *Construction and assembly instructions GN 115*  
→ Main Catalogue Page 859
- *Stainless Steel-Hygienic latches GN 115 (Operation with key)*  
→ Main Catalogue Page 863
- *IP Protection classes* → Page 327

How to order

**GN 115-SG-18-NI**

<b>1</b>	Type
<b>2</b>	Latch distance A
<b>3</b>	Material