

Stainless Steel-Latches

Operation with key, not lockable













V

Type

Operation with triangular spindle (DK7)

VK7 Operation with square spindle A/F7

VK8 Operation with square spindle A/F8

SCH Operation with slot

VDE Operation with double bit



O-ring





Type SCH



Type **VDE**



Riegelabs	stand A												
6	10	14	18	20	22	24	26	28	30	34	38	40	50

Specification

Corrugated

spring washer

Type DK



- Latch Stainless Steel AISI 304
- Protection class IP 65
 Stainless Steel characteristics → Page 1144
- RoHS compliant

Accessory

Keys 119.2 → Page 870

Information

NI

Stainless Steel-Latches GN 115 lock by a turning operation limited to 90° which moves the locking behind the door frame. The bevels of the locking ease the closing of the door.

Latches with different cranks cover a range A from 6 to 28 mm.

The operating bolt is fitted with an O-ring for sealing.

Stainless Steel-Latches GN 115 are supplied with loosely enclosed locking.

see also...

- Construction and assembly instructions GN 115 → Page 859
- Latches GN 115 (Steel zinc plated) → Page 858
- Protective caps GN 120 → Page 868
- Stainless Steel-Hygienic latches GN 115 → New products
- Opening handles GN 320 → Page 869
- IP Protection classes → Page 1137

How to order	1	Туре
1 5 3	2	Latch distance A
GN 115-DK-18-NI	3	Material