



Length l	d ₁ H7 Bore	s H11 Square	d ₂	d ₃	h ₁	h ₂ ≈	h ₃	h ₄	h ₅ ≈	∅ Retractable handle GN 798.3
80	B 10	V 10	23	29	20	3	26	4,3	43	16
100	B 12	V 12	26	34	24	4,5	30	4,2	57,5	18
125	B 14	V 14	28	36	31	9	37	4,2	76,5	24

Specification

- Body
Aluminium
 - plastic coated
black, RAL 9005, textured finish ● **SW**
 - silver, RAL 9006, textured finish ● **SR**
 - hub machined
- Hub cover
light grey
- Retractable handles GN 798.3
 - Plastic, Technopolymer
black, matt finish
 - Retractable mechanism
Steel, blackened
- Square DIN 79 → Page 316
- Cross hole GN 110 → Page 317
- ISO-Fundamental Tolerances → Page 323
- RoHS-compliant

On request

- with retractable handle GN 798.5
→ Main Catalogue Page 23
(retractable mechanism Stainless Steel)

Information

The handpiece of the cranked handle GN 472.3 is locked in a tapered bore in the operating position.

For tilting, the handle must first be pulled out of the taper in axial direction.

A compression spring holds the handle in both end positions. When folded out, it automatically re-engages.

How to order

GN 472.3-100-V12-SR

- | | |
|---|---------------------|
| 1 | Length l |
| 2 | s (d ₁) |
| 3 | Colour |