



ROSTFREI
Inox
Stainless
Steel

Inch
sizes
available

3 Type
AS with external hexagon
IS with internal hexagon

Range extended!

1 2 3

l ₁		d ₁		l ₂						d ₃	d ₄	h ₁	h ₂	h ₃	h ₄ Stroke	A/F ₁	A/F ₂	
30	M 3	-		6	8	10	12	16	-	-	10	13	24,5	4	31	3,5	3	7
30	M 4	-		12	16	20	25	32	-	-	10	13	24,5	4	31	3,5	3	7
30	M 5	M 6		12	16	20	25	32	40	50	10	13	24,5	4	31	3,5	3	7
45	M 4	-		12	16	20	25	32	-	-	10	13	24,5	4	34	3,5	3	7
45	M 5	M 6		12	16	20	25	32	40	50	10	13	24,5	4	34	3,5	3	7
63	M 6	M 8		16	20	25	32	40	50	63	13,5	17,5	31	6,5	45	4	4	10
78	M 8	M 10		20	25	32	40	50	63	80	16	21	36	8	54	4	4	11
92	M 10	M 12		20	25	32	40	50	63	80	19	24	43	11	64	4	5	13

Specification

- GN 300.5**
Handle
Precision casting
- Stainless Steel AISI CF-8
- matt shot-blasted
- GN 300.6**
Handle
Stainless Steel
Precision casting
- Stainless Steel AISI CF-8
- electropolished
- Threaded stud, Stainless Steel AISI 303
- Retaining screw, Stainless Steel AISI 303
- Spring, Stainless Steel AISI 301
- *Stainless Steel characteristics* → Page 334
- RoHS compliant

Information

Adjustable hand levers GN 300.5 with full Stainless Steel-Handle, correspond to applications where „agressive“ surrounding conditions are given, or where stainless steel materials are prescribed such as in food processing or chemical industry.

Retaining screws with hexagon head (Type AS) comply with the requirement „prevents water from accumulating“.

Adjustable hand levers have proved to be ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

St. Steel-Hand lever, matt shot-blasted	1	l ₁
	2	d ₁
GN 300.5-63-M8-32-IS	3	l ₂
	4	Type

St. Steel-Hand lever, electropolished	1	l ₁
	2	d ₁
GN 300.6-92-M12-50-AS	3	l ₂
	4	Type