



ROSTFREI Rost free
Inox Stainless Steel
Inch sizes available

3 Type
AS with external hexagon
IS with internal hexagon

Range extended!



1 l_1	2 d_1	d_3	d_4	h_1	h_2	h_3	h_4 Stroke	A/F ₁	A/F ₂	t min.		
30	M 3	-	-	10	13	24,5	4	31	3,5	3	7	7
30	M 4	M 5	M 6	10	13	24,5	4	31	3,5	3	7	8
45	M 4	M 5	M 6	10	13	24,5	4	34	3,5	3	7	8
63	M 6	M 8	-	13,5	17,5	31	6,5	45	4	4	10	11
78	M 8	M 10	-	16	21	36	8	54	4	4	11	14
92	M 10	M 12	-	19	24	43	11	64	4	5	13	17

Specification

- GN 300.5**
Handle
Precision casting
- Stainless Steel AISI CF-8
- matt shot-blasted
- GN 300.6**
Handle
Stainless Steel
Precision casting
- Stainless Steel AISI CF-8
- electropolished
- Threaded bushing
Stainless Steel AISI 303
- Retaining screw
Stainless Steel AISI 303
- Spring
Stainless Steel AISI 301
- Stainless Steel characteristics → Page 334
- RoHS compliant

Information

Adjustable hand levers GN 300.5 with full Stainless Steel-Handle, correspond to applications where „agressive“ surrounding conditions are given, or where stainless steel materials are prescribed such as in food processing or chemical industry.

Retaining screws with hexagon head (Type AS) comply with the requirement „prevents water from accumulating“.

Adjustable hand levers have proved to be ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

Pulling the lever, disengages the serrations and allowing it to be swivelled to the ideal clamping position. On releasing the lever the serrations automatically re-engage.

St. Steel-Hand lever, matt shot-blasted	1 l_1
GN 300.5-78-M10-AS	2 d_1
	3 Type

St. Steel-Hand lever, electropolished	1 l_1
GN 300.6-92-M12- IS	2 d_1
	3 Type