



**3 Type**

- A** Mounting from the back (threaded blind bore)
- B** Mounting from the operator's side (only for d1=28)

**1** **2**

d <sub>1</sub>	Length l ±0,25								d <sub>2</sub>	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub>	b <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub>	t min.
20	180	200	250	300	350	400	-	M 6	24	12	42	54	42	54	12	
28	200	250	300	350	400	500	600	M 8	25	14	50	66	50	66	15	
30	200	300	350	400	500	600	1000	M 8	27	17	51	68	51	68	15	

**Specification**

**4**

- Handle tube  
Aluminum (wall thickness 1,5)
- Handle shanks  
Zinc die casting
- Tube **SW**  
plastic coated  
black, RAL 9005, textured finish  
Handle shanks plastic coated  
black, RAL 9005, textured finish
- Tube, anodized, natural color **EL**  
Handle shanks plastic coated  
black, RAL 9005, textured finish
- Tube, anodized, natural color **ES**  
Handle shanks plastic coated  
silver, RAL 9006, textured finish
- Cover caps  
Plastic, light grey
- Cap (Type B)  
Plastic (Technopolymer)  
black (for SW / EL)  
light grey (for ES)
- Load rating information → Page XYZ
- RoHS compliant

**Information**

The handle tube of the GN 333 tubular handles can be screwed to the handle bases without further machining or processing, allowing **special lengths** to be realised easily.

A typical application area for tubular handles GN 333 are double-winged doors at machines or devices.

Further handle shanks can be added for very long tubular handles. Individual handle shanks for tubular handles Ø 28 (type A) are available under GN 333.8 → Page 135.

see also...

- Tubular handles GN 333.1 (straight) → Page 130
- Tubular handles GN 332 (with power switching function) → Page 138
- Assembly sets for profile systems 30 / 40 GN 965 → Page XYZ
- Assembly sets for profile systems 30 / 40 / 45 GN 968 → Page XYZ

How to order

**GN 333-28-600-A-EL**

1	d <sub>1</sub>
2	Length l
3	Type
4	Finish