



Inch sizes available

3 Type

- E angled lever
- D straight lever

1 2

d ₁	d ₂ Thread		d ₃	d ₄	d ₅	h ₁	h ₂	h ₃	h ₄		h ₅ Stroke	l ₂		l ₃	t min.
	M 6	M 8							Type E	Type D		Type E	Type D		
21	M 6	M 8	13,5	8	20	37	34,5	4,5	62	39	3	75	81	70	11
24	M 8	M 10	16	10	25	44	41	6,5	78	47	3,5	101	108	96	14
28	M 10	M 12	19	12	30	53	49	8,5	93	56	4	116	124	110	17
33	M 12	M 16	23	12	32	60	56	10,5	105	65	4,5	131	140,5	124	22

Specification

- Steel blackened
- Ball knobs DIN 319 Plastic, Duroplast black, shiny finish
- RoHS compliant

Information

Safety tension levers GN 312 are used on such applications where a thoughtless or mistaken releasing or re-positioning of the tension lever could lead to an accident.

The lever in its rest position is not connected with the internal spindle and can be rotated unhindered.

The tension lever engages in the serration only after pushing it down, thus allowing clamping or unclamping.

The „freewheel“ position is re-established as soon as the handle is released.

How to order

GN312-21-M8-E

- 1 d₁
- 2 d₂
- 3 Type