



Inch sizes available

**4 Type**

- E angled lever
- D straight lever

1 2 3

d <sub>1</sub>	d <sub>2</sub>	l <sub>1</sub>		d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub>		h <sub>5</sub>	l <sub>2</sub>		l <sub>3</sub>					
										Type E	Type D	Stroke	Type E	Type D						
21	M 8	16	20	25	32	40	50	63	13,5	8	20	37	34,5	4,5	62	39	3	75	81	70
24	M 10	20	25	32	40	50	63	80	16	10	25	44	41	6,5	78	47	3,5	101	108	96
28	M 12	20	25	32	40	50	63	80	19	12	30	53	49	8,5	93	56	4	116	124	110
33	M 16	32	40	50	63	80	-	-	23	12	32	60	56	10,5	105	65	4,5	131	140,5	124

**Specification**

- Steel blackened  
Threaded stud  
Tensile strength class 5.8 (500 N/mm<sup>2</sup>)
- Ball knobs DIN 319  
Plastic, Duroplast black, shiny finish
- RoHS compliant

**Information**

Safety tension levers GN 312 are used on such applications where a thoughtless or mistaken releasing or re-positioning of the tension lever could lead to an accident.

The lever in its rest position is not connected with the internal spindle and can be rotated unhindered.

The tension lever engages in the serration only after pushing it down, thus allowing clamping or unclamping.

The „freewheel“ position is re-established as soon as the handle is released.

**How to order**

GN312-24-M10-32-E

- 1 d<sub>1</sub>
- 2 d<sub>2</sub>
- 3 l<sub>1</sub>
- 4 Type