



**3 Type**

- A Semi-spherical pad
- B Pointed pad

**1**

**2**

d <sub>1</sub>	l <sub>1</sub> Nominal length					d <sub>2</sub>	l <sub>2</sub>	l <sub>3</sub>	r	A/F
M 5	8	12	16	20	-	3	1	0,5	2,5	2,5
M 6	12	16	20	25	-	4	1,8	0,8	3	3
M 8	12	16	20	25	32	6	2,5	1	5	4
M 10	16	20	25	32	40	8	3,5	1,5	6	5

**Specification**

- Steel
  - Tensile strength class 5.8 (500 N/mm<sup>2</sup>)
  - blackened
- Thrust pad hardened
- RoHS compliant

**Information**

Grub screws GN 913.2 with hardened spherical pad (Type A) are used in such cases where point contact is required. They are a lower cost alternative to ball point screws GN 605.

Grub screws GN 913.2 with hardened pointed pad (Type B) offer an alternative form of finish.

see also...

- Ball point screws GN 605 (with full ball) → Page 524
- Grub screws GN 913.3 / GN 913.5 (with brass / plastic pad) → Page 520 / 521

How to order

**GN913.2-M6-20-B**

- 1** d<sub>1</sub>
- 2** l<sub>1</sub>
- 3** Type