



Rostfrei
Inox
Stainless
Steel

3 Type

- A** without bore
- E** with threaded blind bore
- D** with threaded through bore
- C** with plain blind bore H7

1 d_1	2 d_2 Thread Type E / D	2 d_3 H7 Bore Type C	d_4	h_1	h_2	t_1 min.	t_2
40	M 6	-	18	26	15	12	13
40	M 8	B 8	18	26	15	15	13
50	M 8	-	21	30	17	15	16
50	M 10	B 10	21	30	17	18	16
60	M 10	-	25	35	18	18	20
60	M 12	B 12	25	35	18	22	20

Specification

- **GN 5345**
 - Stainless Steel AISI 303
 - matt blasted
- **GN 5345.4**
 - Stainless Steel AISI 316L (A4)
 - matt blasted
- *Cross holes GN 110 → Page 317*
- *Stainless Steel characteristics → Page 334*
- *ISO-Fundamental tolerances → Page 323*
- **RoHS compliant**

On request

- highly polished (PL)

Information

Stainless Steel-Three-lobe knobs GN 5345 / GN 5345.4 have a smooth and sealed surface. They are particularly suitable for use where hygiene requirements are high. Their shape allows relatively high torques to be applied.

Stainless Steel-Three-lobe knob AISI 303	
1	d_1
2	d_3 (d_2)
3	Type
GN 5345-60-B12-C	

Stainless Steel-Three-lobe knob AISI 316L (A4)	
1	d_1
2	d_2 (d_3)
3	Type
GN 5345.4-40-M8-E	