



Inch sizes available

¹ l ₁	² d ₁ Thread			² d ₂ H7 Bore	d ₃	d ₄	h ₁	h ₂	h ₃	h ₄ Stroke	t min.	
30	M 3	-	-	-	-	10	13	24,5	4	31	3,5	7
30	M 4	M 5	M 6	B 5	B 6	10	13	24,5	4	31	3,5	9
45	M 4	M 5	M 6	B 5	B 6	10	13	24,5	4	34	3,5	9
63	M 6	M 8	-	B 8	-	13,5	17,5	31	6,5	45	4	11
78	M 8	M 10	-	B 8	B 10	16	21	36	8	54	4	14
92	M 10	M 12	-	B 12	-	19	24	43	11	64	4	17
108	M 12	M 14	M 16	B 12	B 16	23	30	50,5	12	75	5	22

Specification

- Handle
Zinc die casting
- Plastic coated
black, RAL 9005, textured finish
black, RAL 9011, silk finish
orange, RAL 2004, textured finish
red, RAL 3000, textured finish
silver, RAL 9006, textured finish
- chrome-plated
- uncoated
slide grinded
- Threaded bushing and retaining screw
Steel
- Tensile strength class 5
- blackened
- ISO-Fundamental tolerances → Page 1749
- RoHS compliant

³

Information

Adjustable hand levers GN 300 are ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

Pulling the lever, disengages the serrations and allowing it to be swivelled to the ideal clamping position. On releasing the lever the serrations automatically re-engage.

see also...

- Adjustable hand levers GN 300.1 (bushing Stainless Steel) → Page 322
- Adjustable Stainless Steel-Hand levers GN 300.5 (matt shot-blasted) → Page 324
- Flat adjustable hand levers GN 302 → Page 334
- Adjustable hand levers GN 300.4 (with increased clamping force) → Page 332
- Adjustable hand levers GN 303 (with push button) → Page 328

How to order

GN300-92-M12-SR

¹	l ₁
²	d ₁ (d ₂)
³	Colour (Finish)