



ROSTFREI
Inox
Stainless
Steel

Inch
sizes
available

4 Type
AS with external hexagon
IS with internal hexalobular

1		2		3													
l_1	d_1	l_2		d_3	d_4	h_1	h_2	h_3	h_4	Stroke							
30	M 3	-	6	8	10	12	16	-	-	10	13	24,5	4	31	3,5		
30	M 4	-	12	16	20	25	32	-	-	10	13	24,5	4	31	3,5		
30	M 5	M 6	12	16	20	25	32	40	50	10	13	24,5	4	31	3,5		
45	M 4	-	12	16	20	25	32	-	-	10	13	24,5	4	34	3,5		
45	M 5	M 6	12	16	20	25	32	40	50	10	13	24,5	4	34	3,5		
63	M 6	M 8	16	20	25	32	40	50	63	13,5	17,5	31	6,5	45	4		
78	M 8	M 10	20	25	32	40	50	63	80	16	21	36	8	54	4		
92	M 10	M 12	20	25	32	40	50	63	80	19	24	43	11	64	4		

Specification

- GN 300.5**
 Handle
 Stainless Steel-Precision casting
 - AISI CF-8
 - matt shot-blasted
- GN 300.6**
 Handle
 Stainless Steel-Precision casting
 - AISI CF-8
 - electropolished
- Threaded stud
 Stainless Steel AISI 303
- Retaining screw
 Stainless Steel AISI 303
- Spring
 Stainless Steel AISI 301
- Stainless Steel characteristics → Page 1489
- RoHS compliant

Information

Adjustable hand levers GN 300.5 with full Stainless Steel-Handle, correspond to applications where „agressive“ surrounding conditions are given, or where stainless steel materials are prescribed such as in food processing or chemical industry.

Retaining screws with hexagon head (Type AS) comply with the requirement „prevents water from accumulating“.

Adjustable hand levers have proved to be ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

How to order (matt shot-blasted)

1	l_1
2	d_1
3	l_2
4	Type

GN 300.5-63-M8-32-IS

How to order (electropolished)

1	l_1
2	d_1
3	l_2
4	Type

GN 300.6-92-M12-50-AS