



ROSTFREI  
Inox  
Stainless  
Steel

1 2 3

1		2		3															
l <sub>1</sub>	d <sub>1</sub>			l <sub>2</sub>								d <sub>3</sub>	d <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub>	Stroke	
30	M 3	-		6	8	10	12	16	-	-	-	10	13	26,5	4	31	3,5		
30	M 4	-		12	16	20	25	32	-	-	-	10	13	26,5	4	31	3,5		
30	M 5	M 6		12	16	20	25	32	40	50	-	10	13	26,5	4	31	3,5		
45	M 4	-		12	16	20	25	32	-	-	-	10	13	26,5	4	35	3,5		
45	M 5	M 6		12	16	20	25	32	40	50	-	10	13	26,5	4	35	3,5		
63	M 6	M 8		12	16	20	25	32	40	50	63	13,5	17,5	32,5	6,5	45	4		
63	M 10	-		20	25	32	40	50	63	-	-	13,5	17,5	32,5	6,5	45	4		
78	M 8	M 10		16	20	25	32	40	50	63	80	16	21	37,5	8	55	4		

**Specification**

4 5

- Handle  
Zinc die casting
- plastic coated  
black, RAL 9005  
textured finish ● SW
- Push button  
Plastic  
black, RAL 9005 ● S  
orange, RAL 2004 ● O  
grey, RAL 7035 ● G
- Threaded insert  
Stainless Steel AISI 303
- Pin for push button  
Stainless Steel
- *Stainless Steel characteristics* → Page 1144
- **RoHS compliant**

**On request**

- Handle in colours of GN 300

**Information**

Adjustable hand levers GN 303.1 are ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

The push button is a design element that offers an easy disengagement. Its use is limited to applications where dismantling of the lever for installation is not required.

see also...

- *Adjustable hand levers GN 303 (insert steel, blackened)* → Page 203

**How to order**

1	l <sub>1</sub>
2	d <sub>1</sub>
3	l <sub>2</sub>
4	Handle colour
5	Push button colour

1 2 3 4 5  
**GN303.1-63-M8-32-SW-G**