



3 Type

- M** Straight lever
- N** Angled lever

1

2

d₁	d₂ Thread	d₃	d₄	d₆	h₁	h₂	h₃ ≈	l₂	l₃ ≈	t min.	
20	M 6	M 8	13,5	20	8,5	25	8	46	74	70	12
25	M 8	M 10	16	25	11	29	8	58	93	87	15
28	M 10	M 12	19	30	13	33,5	10,5	70,5	116	109	18

Specification

- Steel
blackened
Threaded insert
Tensile strength class 5.8 (500 N/mm²)
- Ball knobs DIN 319
Plastic, Technopolymer
black, shiny finish
- RoHS compliant

Information

Adjustable clamping levers GN 6337.3 have proved to be ideal whenever parts have to be clamped in a confined space or a particular lever position is required. The insert is connected with the lever via serrations in the ball bore which can be disengaged.

Pushing the lever down, disengages the serrations and the lever can be swivelled to the ideal clamping position. Engagement is achieved by releasing the lever.

Should a rotation of 360° not be possible, the insert can be lightly screwed in (after the lever is disengaged) via a slot in the knurled screw.

see also...

- Ball levers DIN 6337 (not adjustable) → Page 247

How to order

GN6337.3-28-M12-N

- 1** d₁
- 2** d₂
- 3** Type