



- 3 Type**
- C** angled lever with plain bore H7
  - E** angled lever with threaded bore
  - B\*** straight lever with plain bore H7
  - D\*** straight lever with threaded bore

Steel												
d <sub>1</sub>	d <sub>2</sub> Thread Type E / D	d <sub>3</sub> H7 Bore Type C / B	d <sub>4</sub>	d <sub>5</sub>	h <sub>1</sub>	h <sub>2</sub> ≈ Type C Type E	Type B Type D	l <sub>1</sub> ≈ Type C Type E	Type B Type D	l <sub>2</sub> ≈	t <sub>1</sub> min.	t <sub>2</sub> min.
22	M 10	B 10	8	20	37	67	40,5	89,5	96	85	15	19
25	M 12	B 12	10	25	42	76	47	100,5	107,5	95	18	21
28	M 12	B 12	12	30	47	87	53	114	122	108	18	23
32	M 16	B 16	12	32	52	98	59	133	142	126	23	28
36	M 16	B 16	14	35	58	108	64,5	146	156	138	24	28
40	M 20	B 20	16	40	64	120	72	162,5	174	154	27	30

Stainless Steel									
d <sub>1</sub>	d <sub>2</sub> only type E	d <sub>4</sub>	d <sub>5</sub>	h <sub>1</sub>	h <sub>2</sub> ≈	l <sub>1</sub> ≈	l <sub>2</sub> ≈	t <sub>1</sub> min.	
22	M 8	8	20	37	67	89,5	85	18	
25	M 10	10	25	42	76	100,5	95	18	
28	M 12	12	30	47	87	114	108	20	
32	M 16	12	32	52	98	133	126	25	

\* not available from stock, requires a minimum order quantity

**Specification**

- Steel —
- Stainless Steel **NI**
  - AISI 303
  - matt shot-blasted
- Ball knobs DIN 319  
Plastic, Duroplast  
black, shiny finish
- Cross holes GN 110 → Page 1127
- ISO Fundamental Tolerances → Page 1132
- Stainless Steel characteristics → Page 1144
- RoHS compliant

**Information**

Tension levers GN 212 are used as clamping element as well as operating levers.

see also...

- Adjustable tension levers GN 212.3 (Steel, blackened) → Page 222
- Adjustable Stainless Steel-Tension levers GN 212.5 → Page 224

How to order (Steel)	
1	d <sub>1</sub>
2	d <sub>3</sub> (d <sub>2</sub> )
3	Type

**GN 212-28-B12-C**

How to order (Stainless Steel)	
1	d <sub>1</sub>
2	d <sub>2</sub>
3	Type
4	Material

**GN 212-25-M10-E-NI**