



 Inch sizes available

3 Type

- E angled lever
- D straight lever

1

2

d ₁	d ₂ Thread		-	d ₃	d ₄	d ₅	h ₁	h ₂	h ₃	h ₄ ≈		h ₅ Stroke	l ₂ ≈		l ₃ ≈	t min.
	M 6	M 8								Type E	Type D		Type E	Type D		
21	M 6	M 8	-	13,5	8	20	33,5	31	1	59	36	4	75	80,5	70	11
24	M 8	M 10	-	16	10	25	40	37	2,5	75	43,5	4,5	101	108	96	14
28	M 10	M 12	-	19	12	30	48,5	44,5	4,5	89	52,5	4,5	116	124	110	17
33	M 12	M 14	M 16	23	12	32	55	51,5	6	100,5	60	5,5	131,5	140,5	124	22
40	M 16	M 20	-	28	14	35	68	64	6	118	71,5	5,5	148	158	138	36

Specification

- Steel blackened
- Ball knobs DIN 319 Plastic, Duroplast black, shiny finish
- RoHS compliant

Information

Adjustable tension levers GN 212.3 have proved to be ideal whenever parts have to be clamped in a confined space or a particular lever position is required. The threaded insert is connected with the hub via serrations which can be disengaged.

Pulling the lever, disengages the serrations and allowing it to be swivelled to the ideal clamping position. On releasing the lever it will automatically re-engage.

see also...

- [Adjustable Stainless Steel-Tension levers GN 212.5 → Page 224](#)
- [Safety tension levers GN 312 → Page 226](#)

How to order

GN 212.3-24-M8-D

1 d₁
2 d₂
4 Type