



ROSTFREI Rost frei
Inox Stainless Steel
Inch sizes available

4 Type
E angled lever

1 d ₁	2 d ₂ Thread	3 l ₁								d ₃	d ₄	d ₅	h ₁	h ₃	h ₄ Stroke	l ₂
21	M 8	16	20	25	32	40	50	63	13,5	8	20	33,5	1	4	70	
24	M 10	20	25	32	40	50	63	80	16	10	25	40	2,5	4,5	96	
28	M 12	25	32	40	50	63	80	-	19	12	30	48,5	4,5	4,5	110	

Specification

- Stainless Steel AISI 303 matt shot-blasted
- Ball knobs DIN 319 Plastic, Duroplast black, shiny finish
- *Stainless Steel characteristics* → Page 1144
- RoHS compliant

On request

- straight lever (90°)

Information

Adjustable tension levers GN 212.5 have proved to be ideal whenever parts have to be clamped in a confined space or a particular lever position is required. The threaded insert is connected with the hub via serrations which can be disengaged.

Pulling the lever, disengages the serrations and allowing it to be swivelled to the ideal clamping position. On releasing the lever it will automatically re-engage.

see also...

- *Adjustable tension levers GN 212.3 (Steel, blackened)* → Page 223

How to order

1 d ₁	
2 d ₂	
3 l ₁	
4 Type	

GN 212.5-28-M12-25-E

1.1
1.2
1.3
1.4
1.5
1.6
1.7
1.8
1.9