



**4 Type**  
 D straight lever  
 E angled lever

1 2 3

d <sub>1</sub>	d <sub>2</sub> Thread	l <sub>1</sub>				d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub> ≈	h <sub>5</sub> Stroke	l <sub>2</sub>				
32	M 8	12	16	20	25	32	40	50	-	13,5	8	20	20,5	1,5	12,5	36	4	100
36	M 10	16	20	25	32	40	50	63	80	16	10	25	24,5	2	15	45	4,5	120
40	M 12	25	32	40	50	63	80	-	-	19	12	30	30	4	19	53	4,5	130
45	M 16	32	40	50	63	80	-	-	-	23	12	32	35,5	4	24	64	5	145

**Specification**

- Stainless Steel AISI 303 matt shot-blasted
- Plane surface with natural coloured, anodized Aluminium-disc
- Ball knobs DIN 319 Plastic, Duroplast black, shiny finish
- *Stainless Steel characteristics* → Page 1144
- **RoHS compliant**

**Information**

The overall height of Stainless Steel-tension levers GN 125.5 is reduced to a minimum.

As all other adjustable levers, they are ideal whenever parts have to be clamped in a confined space, or a particular lever position is required. The threaded insert is connected with the hub via serrations which can be disengaged.

Pulling the lever, disengages the serrations and the lever can be swivelled to the ideal clamping position. On releasing the lever it will automatically re-engage.

see also...

- *Adjustable flat tension levers GN 125 (Steel, blackened)* → Page 231

How to order

GN 125.5-32-M8-20-D

- 1 d<sub>1</sub>
- 2 d<sub>2</sub>
- 3 l<sub>1</sub>
- 4 Type

1.1  
1.2  
1.3  
1.4  
1.5  
1.6  
1.7  
1.8  
1.9