



Internationaler
Designpreis
Baden-Württemberg

b	Length l ±0,25						Finish WSA			a	d	h	r	t min.
	100	112	117	120*	-	-	100	112	-					
20	128	160	180*	200	235*	-	128	160	-	13	M 6	49	13	10
26	112	117	120	125	128	-	128	-	-	17	M 8	55	17	12
26	160	179	192	300	400	500	160	192	300	17	M 8	57	17	12

* suitable for 19" rack and enclosure layout

Specification

- Aluminium
 - plastic coated
 - black, RAL 9005, textured finish ● **SW**
 - black, RAL 9005, textured finish ● **SWU**
 - UV-resistant
 - red, RAL 3000, textured finish ● **RS**
 - silver, RAL 9006, textured finish ● **SR**
 - white, RAL 9016, antimicrobial ● **WSA**
 - anodized, natural colour ● **EL**
 - blank ● **BL**
 - tumbled
- Load rating information → Page 342
- RoHS compliant

Information

GN 565 cabinet „U“ handles are made from a bent aluminum profile and have excellent stability and ergonomic design. Due to the production process, special designs can be supplied even in relatively small quantities.

In addition to the standard surfaces, these cabinet „U“ handles are also available with a functional coating.

The **SWU** version is coated with a highly weather-resistant and UV-protective powder coating system, making this version excellent for outdoor use.

The **WSA** version has a powder coating based on zinc molybdate, which gives it antimicrobial properties. The principle of action, which is activated by the presence of moisture, demonstrably reduces the growth of viruses, bacteria, and fungi within 24 hours, so that contaminated surfaces ultimately have less than 0.2% of the original number of microbes.

Standard elements with antimicrobial plastic coating are primarily used in the health care sector and in public buildings, such as airports, train stations, stadiums, etc.

see also...

- Inclined Cabinet „U“ handles GN 565.2 → Main Catalogue Page 64
- Stainless Steel-Cabinet „U“ handles GN 565.5 → Page 32
- Cabinet „U“ handles GN 725 (Plastic) → Main Catalogue Page 68

How to order

GN 565-20-100-SW

1	b
2	Length l
3	Finish