



Bore for socket head cap screw DIN 912



2 Type

- A** Mounting from the back (threaded blind bore)
- B** Mounting from the operator's side

¹ $l_1 \pm 0,25$ GN 728	¹ $l_1 \pm 0,25$ GN 728.5	b	d₁	d₂	d₃	h₁	h₂	l₂	l₃	s	t₁ min.	t₂
120	120	22,5	M 6	6,4	11	42,5	6,5	147	108	8	10	6,5
180	-	27	M 8	8,4	13,5	47,5	7,5	214	165	10	12	8,5

Specification

- **GN 728**
Aluminium pressure die casting
 - plastic coated
 - black, RAL 9005, textured finish
 - silver, RAL 9006, textured finish
 - blank
 - tumbled
- **GN 728.5**
Stainless Steel AISI CF-8
 - Precision casting
 - matt shot-blasted
- *Stainless Steel characteristics* → Page 1144
- *Load rating information* → Page 1153
- **RoHS compliant**

- ³ ● **SW**
- **SR**
- **BL**

Information

The installation of cabinet „U“ handles GN 728 / GN 728.5 can be carried out from the back (Type A) as well as from the operator's side (Type B). The hole centers dimension is identical on all variants. As a result they can be mounted in pairs opposite each other.

see also...

- *Cabinet „U“ handles GN 528 (Plastic)* → Page 70

Cabinet „U“ handle ¹ ² ³ GN 728-120-A-SW	1	l_1
	2	Type
	3	Finish

Stainless Steel-Cabinet „U“ handle ¹ ² GN 728.5-120-B	1	l_1
	2	Type