



d <sub>1</sub>	Length l ±0,25	Finish WSA	d <sub>2</sub>	h	r	t min.
20	200	200	M 8	68	22	15
20	250	250	M 8	68	22	15
20	300	300	M 8	68	22	15
20	350	-	M 8	68	22	15
28	250	250	M 10	78	32	15
28	300	300	M 10	78	32	15
28	350	-	M 10	78	32	15
28	400	400	M 10	78	32	15

## Specification

- Aluminium **AL**
- d<sub>1</sub> = 20: Solid material
- d<sub>1</sub> = 28: Tube-Ø 28 x 4
- plastic coated
  - black, RAL 9005, textured finish ● **SW**
  - silver, RAL 9006, textured finish ● **SR**
  - white, RAL 9016, antimicrobial ○ **WSA**
- blank ○ **BL**
- tumbled
- Threaded bushings Aluminium
- Load rating information → Page 1150
- RoHS compliant

## Information

426 cabinet „U“ handles are made from a bent aluminum profile and have excellent stability and ergonomic design. Due to the production process, special designs can be supplied even in relatively small quantities.

In addition to the standard surfaces, these cabinet „U“ handles are also available with a functional coating.

The **WSA** version has a powder coating based on zinc molybdate, which gives it antimicrobial properties. The principle of action, which is activated by the presence of moisture, demonstrably reduces the growth of viruses, bacteria, and fungi within 24 hours, so that contaminated surfaces ultimately have less than 0.2% of the original number of microbes.

Standard elements with antimicrobial plastic coating are primarily used in the health care sector and in public buildings, such as airports, train stations, stadiums, etc. Cabinet „U“ handles GN 426 are produced from profiled alumin

see also...

- Stainless Steel-Cabinet „U“ handles GN 426.5 → Page 95

### How to order

1 2 3 4  
**GN 426-AL-28-300-SW**

<b>1</b>	<b>Material</b>
<b>2</b>	<b>d<sub>1</sub></b>
<b>3</b>	<b>Length l</b>
<b>4</b>	<b>Finish</b>