



d <sub>1</sub>	Length l ±0,25	d <sub>2</sub>	h <sub>1</sub>	h <sub>2</sub>	r	t min.
20	200	M 8	105	68	22	15
20	300	M 8	105	68	22	15
28	250	M 10	125	78	32	15
28	350	M 10	125	78	32	15
28	500	M 10	125	78	32	15

Specification

- Aluminium **AL**
  - d<sub>1</sub> = 20: Solid material
  - d<sub>1</sub> = 28: Tube-Ø 28 x 4
  - plastic coated
    - black, RAL 9005, textured finish ● **SW**
    - silver, RAL 9006, textured finish ● **SR**
  - blank ○ **BL**
  - tumbled
- Threaded bushings Aluminium
- Load rating information → Page 1150
- RoHS compliant

Information

Cabinet „U“ handles GN 426.1 are produced from profiled aluminium extrusions.

The manufacturing process (bending) allows the production of **special lengths** in relatively small quantities.

How to order

1 2 3 4  
**GN426.1-AL-28-250-SW**

<span style="color:red">1</span>	Material
<span style="color:red">2</span>	d <sub>1</sub>
<span style="color:red">3</span>	Length l
<span style="color:red">4</span>	Finish

1.1  
1.2  
1.3  
1.4  
1.5  
1.6  
1.7  
1.8  
1.9