



3 Type

- A** Mounting from the back (threaded blind bore)
- B** Mounting from the operator's side (only for $d_1 = 28$)

1

2

d_1	Length $l \pm 0,25$							d_2	d_3	b_1	b_2	h_1	h_2	t min.
20	180	200	250	300	350	400	-	M 6	-	24	12	42	54	12
28	200	250	300	350	400	500	600	M 8	M 6	25	14	50	66	15
30	200	300	350	400	500	600	1000	M 8	-	27	17	51	68	15

Specification

- Handle tube
Aluminum (wall thickness 1,5)
- Handle shanks
Zinc die casting
- Tube ● **SW**
plastic coated
black, RAL 9005, textured finish
Handle shanks plastic coated
black, RAL 9005, textured finish
- Tube ● **EL**
anodized, natural color
Handle shanks plastic coated
black, RAL 9005, textured finish
- Tube ● **ES**
anodized, natural color
Handle shanks plastic coated
silver, RAL 9006, textured finish
- Cover caps
Plastic, light grey
- Socket button head screws
ISO 7380-M6-20
Steel, black zinc plated
- Hexagon nuts ISO 4032-M6
Steel, zinc plated
- Washers DIN 125
Steel, zinc plated
- Load rating information → Page XYZ
- RoHS compliant

4

Information

The handle tube of the GN 333.1 tubular handles can be screwed to the handle bases without further machining or processing, allowing **special lengths** to be realised easily.

Further handle shanks can be added for very long tubular handles. Individual handle shanks for tubular handles $\varnothing 28$ (type A) are available under GN 333.9 → Page 135.

For type B, socket button head screws, hexagon nuts and washers are included.

see also...

- Tubular handles GN 333 (angled) → Page 136
- Stainless Steel-Tubular handles GN 333.5 → Page 134
- Tubular handles GN 331 (with power switching function) → Page 132
- Assembly sets for profile systems 30 / 40 GN 965 → Page XYZ
- Assembly sets for profile systems 30 / 40 / 45 GN 968 → Page XYZ

How to order

1	d_1
2	Length l
3	Type
4	Finish

GN 333.1-28-400-B-SW