



1.1
1.2
1.3
1.4
1.5
1.6
1.7
1.8
1.9

1	2	3	4	5	6	7	8	9	10
b	d		$l_1 \pm 0,5$	a	h	l_2	l_3	l_4	t min.
36	M 6	M 8	200	24	57	236	164	290	15
36	M 6	M 8	250	24	57	286	214	340	15
36	M 6	M 8	300	24	57	336	264	390	15
36	M 6	M 8	400	24	57	436	364	490	15
36	M 6	M 8	500	24	57	536	464	590	15
36	M 6	M 8	600	24	57	636	564	690	15

Specification

- Handle tube
Aluminium
- Handle shanks / Cover cap
plastic
Technopolymer (Polyamide PA)
- glass fibre reinforced
- temperature resistant up to 100 °C
- Tube **SW**
plastic coated
black, RAL 9005, textured finish
Handle shanks / Cover cap
black, matt
- Tube anodized, natural colour **ELS**
Handle shanks / Cover cap
black, matt
- Tube anodized, natural colour **ELG**
Handle shanks / Cover cap
light grey, matt
- Bushing
Steel, zinc plated
- Load rating information → Page 1149
- RoHS compliant



Information

Characteristic for the design of the GN 366 oval handles: Tube and handle shank are made in the same elliptical profile.

see also...

- Oval tubular handles GN 334 → Page 114

How to order		1	b
		2	d
		3	l_1
		4	Finish
GN366-36-M8-400-ELS			