



**Rost**  
fret  
Inox  
Stainless  
Steel

1.1  
1.2  
1.3  
1.4  
1.5  
1.6  
1.7  
1.8  
1.9

<b>d<sub>1</sub></b>	<b>l<sub>1</sub> ±0,5</b>	<b>b</b>	<b>d<sub>2</sub></b>	<b>h</b>	<b>l<sub>2</sub></b>	<b>l<sub>3</sub></b>	<b>l<sub>4</sub></b>	<b>l<sub>5</sub></b>	<b>l<sub>6</sub></b>
30	200	18	M 8	60	230	170	265	85	17
30	250	18	M 8	60	280	220	315	85	17
30	300	18	M 8	60	330	270	365	85	17
30	400	18	M 8	60	430	370	465	85	17
30	500	18	M 8	60	530	470	565	85	17
30	600	18	M 8	60	630	570	665	85	17

**Specification**

- Tube Ø 30 x 1,5  
Aluminium / Stainless Steel
- Handle shanks / cover caps  
Plastic (Polyamide PA)  
- glass fibre reinforced  
- temperature resistant up to 100 °C
- Tube Aluminium  
plastic coated  
black, RAL 9005, textured finish ● **SW**  
Handle shanks / cover caps, black, matt
- Tube Aluminium  
anodized, natural colour ● **EL**  
Handle shanks / cover caps, black, matt
- Tube Aluminium  
anodized, natural colour ● **ELG**  
Handle shanks / cover caps, light grey, matt
- Tube Stainless Steel AISI 304  
ground, matt shiny finish ● **NG**  
Handle shanks / cover caps, black, matt
- Load rating information → Page 1153
- RoHS compliant

**3**

**Information**

Owing to their large range of variants and their classic design, GN 666 .1 tubular handles are the perfect choice for many applications.

The mounting screws included allow the installation both from the operator side and the rear side. GN 666.1 and GN 666 tubular handles of identical length are also suitable for double mounting, e.g. for sliding doors.

see also...

- *Stainless Steel-Tubular handles GN 666.5 / GN 666.7 → Page 112*

<b>Tubular handle</b>	<b>1</b> d <sub>1</sub>
<b>GN 666.1-30-600-SW</b>	<b>2</b> l <sub>1</sub>
	<b>3</b> Material / Finish

<b>Stainless Steel-Tubular handle</b>	<b>1</b> d <sub>1</sub>
<b>GN 666.1-30-400-NG</b>	<b>2</b> l <sub>1</sub>
	<b>3</b> Material / Finish