



1	2		3	b	h	l₂	l₃	l₄	t min.	
30	M 6	M 8	l ₁ ±1	400	22	90	440	360	480	15
30	M 6	M 8	500	22	94	540	460	580	15	
30	M 6	M 8	600	22	98	640	560	680	15	

Ausführung

- Handle tube Ø 30 x 1,5
Aluminium / Stainless Steel
- Handle shanks
Aluminium, plastic coated
- Cover caps
Plastic (Polyamide PA)
- glass fibre reinforced
- temperature resistant up to 100 °C
- Tube / Handle shanks Aluminium **● SW**
plastic coated
black, RAL 9005, textured finish
Cover caps, black, matt
- Tube Aluminium **● EL**
anodized, natural colour
Handle shanks
black, RAL 9005, textured finish
Cover caps, black, matt
- Tube Aluminium **● ES**
anodized, natural colour
Handle shanks
silver, RAL 9006, textured finish
Cover caps, light grey, matt
- Tube Stainless Steel **● NG**
AISI 304
ground, matt shiny finish
Handle shanks
black, RAL 9005, textured finish
Cover caps, black, matt
- Load rating information → Page 1152
- RoHS compliant

Information

With their curved type, GN 666.4 tubular arch handles highlight modern-machine design.

The production method used allows special solutions to be realised, e. g. with other radii of curvature or other leg heights.

see also...

- *Stainless Steel-Tubular handles GN 666.5 / GN 666.7 → Page 112*

Tubular arch handle	1	d ₁
	2	d ₂
	3	l ₁
GN 666.4-30-M6-500-EL	4	Material / Finish

Stainless Steel-Tubular arch handle	1	d ₁
	2	d ₂
	3	l ₁
GN 666.4-30-M8-400-NG	4	Material / Finish