



2

| d <sub>1</sub> | d <sub>2</sub> | d <sub>3</sub> | l <sub>1</sub> | l <sub>2</sub> ≈<br>(arrested) | l <sub>3</sub> | l <sub>4</sub> | l <sub>5</sub> |
|----------------|----------------|----------------|----------------|--------------------------------|----------------|----------------|----------------|
| 22             | M 6            | 20             | 73             | 82                             | 22             | 13             | 5,5            |
| 24             | M 6            | 20             | 88             | 97                             | 22             | 13             | 5,5            |
| 25             | M 6            | 20             | 98             | 107                            | 22             | 13             | 5,5            |

**Specification**

- Handle  
Plastic  
Technopolymer (Polyamide PA)  
- temperature resistant up to 90 °C  
- black, matt finish  
- revolving
- Retractable mechanism Steel  
blackened
- *Plastic characteristics* → Page 1141
- **RoHS-compliant**

1

KT

**Information**

Safety retractable handles GN 798.7 are suitable for applications where the handle must not remain in the operating position.

In order to bring the handle into the operating position it has to be turned first through 90° to a stop against a torsion spring and then it is pushed against spring pressure into its hold position.

By maintaining the forward thrust on the handle, the handwheel can easily be rotated.

When releasing the handle, the springs return it back to the retracted position.

**On request**

- Stainless Steel-Safety retractable handles

|              |   |                |
|--------------|---|----------------|
| How to order | 1 | Material       |
|              | 2 | d <sub>1</sub> |

**GN798.7-KT-24**