



3 Type

- D** with plain shaft
- E** with threaded shaft

2

d_1	d_2 h8 Type D ST / AL		d_3 Type E ST / AL		d_4 h13	$l_1 \approx$	l_2	l_3	A/F Internal hexagon
		KT		KT					
16	7	7	M 6	M 6	10	49	11	5,5	3
20	8	8	M 8	M 8	13	61	13	6	4
25	10	10	M 10	M 10	16	75	14	8	5
32	13	13	M 12	M 12	20	95	21	10,5	6
36	16	-	M 16	-	22	106	26	11	8

Specification

- Steel **ST**
zinc plated, blue passivated
- Aluminium **AL**
glossy finish
- Plastic **KT**
Technopolymer (Polyamide PA)
- temperature resistant up to 110 °C
- black, matt finish
- Spindle Steel
zinc plated, blue passivated
- *ISO-Fundamental Tolerances* → Page 1132
- *Plastic characteristics* → Page 1141

1

Information

Revolving handles DIN 98 type D are supplied unassembled so that the shaft can be press fitted or screwed into a tapped blind bore prior to assembly.

During mounting, easy blows with a soft hammer are sufficient to drive the handle into place.

How to order

DIN 98-KT-32-D

- 1** Material
- 2** d_1
- 3** Type