



3 Type

- N** neutral
- M** with arrow
- S** with scale 0...9
20 graduations

1

2

d ₁	d ₂ H8 Bore		d ₃ -0,2	d ₄	d ₅	l ₁	l ₂	l ₃	l ₄	t ₁	t ₂
27	B 6	-	33,5	23,5	M 4	25,5	7,5	10,5	12,5	23,5	7,5
34	B 6	B 8	41	29,5	M 5	29,5	9,5	13,5	13	26,5	9,5
42	B 8	B 10	50	37,5	M 5	33,5	10,5	15,5	15	30,5	11,5

Specification

- Aluminium anodized, natural colour
- Scale (Type S) and arrow (Type M) engraved with laser precision
- Stainless Steel-Grub screw DIN 916 with internal hexagon and serrated point
- ISO-Fundamental Tolerances → Page 1132
- RoHS compliant

Accessory

- Reference flanges GN 723.3 are to be ordered separately

On request

- special graduations see „How to order Graduations“ → Page 337

Information

Control knobs GN 723.4 can be combined with reference flanges GN 723.3 which offer the following advantages:

- they are provided with a reference mark relating to the scale on the control knobs
- they give additional support to the control shaft,
- the version with a friction ring prevents unexpected movement through vibration.

Scale and arrow on the control knobs are indelibly marked and easily legible.

Besides the standard scale (Type S) they can be supplied with any type of graduation.

Regarding design, numbering run, numbering position and numbering sequence of the scale please see the layout for scale knobs on the order sheet „How to order Graduations“ → Page 337

see also...

- Reference flanges GN 723.3 → Page 350
- Clamping elements GN 826 (for adjustable spindles) → New products

How to order

GN 723.4-42-B10-S

1	d ₁
2	d ₂
3	Type



Control knob GN 723.4 combined with a reference flange GN 723.3 → Page 350

