


Counterbored for cap screws DIN 912- M4/5



2 Type

- A** fixing holes parallel to plunger
- B** fixing holes vertical to plunger



| d ₁ | d ₂ | d ₃ | d ₄ | k ±0,1 | l ₁ | l ₂ ≈ | l ₃ | s |
|----------------|----------------|----------------|----------------|--------|----------------|------------------|----------------|----|
| M 12 x 1,5 | 32 | M 5 | 4,5 | 21 | 22 | 26,5 | 9 | 12 |
| M 16 x 1,5 | 46 | M 8 | 5,5 | 32 | 33 | 37 | 13 | 15 |
| M 20 x 1,5 | 46 | M 8 | 5,5 | 32 | 33 | 37 | 13 | 15 |

Specification

- Steel
 - blackened
 - Grub screw GN 913.3 with brass pad
- Stainless Steel AISI 303 **NI**
- Grub screw GN 913.5 with brass pad
- *Stainless Steel characteristics* → Page 1144
- **RoHS compliant**



Information

Mounting blocks GN 612.1 broaden the mounting possibilities and are an added feature for the cam action indexing plungers GN 612 and cam action indexing plungers GN 712 / GN 712.1.

To position the indexing pin of an indexing plunger or cam action indexing plunger, they can also hold GN 412.2 positioning bushings.

see also...

- *Positioning bushings GN 412.2* → Page 454
- *Grub screws GN 913.3 / GN 913.5* → Page 520

| | | |
|---------------------------|---|----------------|
| Steel-Mounting block | 1 | d ₁ |
| GN 612.1-M20x1,5-A | 2 | Type |

| | | |
|--------------------------------|---|----------------|
| Stainless Steel-Mounting block | 1 | d ₁ |
| GN 612.1-M16x1,5-B-NI | 2 | Type |
| | 3 | Material |