



1 d_1 Plunger $-0,05$ Bore $+0,1$ $+0,05$	2		3 d_2	h_1	h_2	k	l_1	l_3	l_4	l_5	s	Spring load in N \approx	
	l_2											initial	end
6	10	16	16	10	4,5	28	46	10	30	40	16	12	32
8	10	16	16	10	4,5	28	46	10	30	40	16	12	32
8	12	18	20	10	4,5	32	57	12	37	45	20	21	58
10	10	16	16	10	4,5	28	46	10	30	40	16	12	32
10	12	18	20	10	4,5	32	57	12	37	45	20	21	58
12	12	18	20	10	4,5	32	57	12	37	45	20	21	58

Specification

- Guide
Zinc die casting
plastic coated
black, RAL 9005, textured finish ● SW
- Plunger
Steel
zinc plated, blue passivated
- Lever
Plastic (Polyamide PA)
- black, matt
- not removable
- Plastic characteristics → Page 331
- RoHS compliant

Information

Cam action indexing plungers GN 612.10 are used in cases where the plunger must not protrude all the time. By rotating the lever through 180° the plunger withdraws itself. The notch allows safe positioning.

see also...

- Range of cam action indexing plungers
→ Main catalogue page 412 / 415
- Spring latches GN 722.2 (Steel) → Main catalogue Page 462
- Spring latches GN 722.3 (Steel) → Main catalogue Page 463
- Cam action indexing plungers GN 612.2 (Steel)
→ Main catalogue page 457
- Guide bushings DIN 172 / DIN 179 → Page 140

How to order	1 d_1
	2 l_2
	3 d_2
	4 Finish

GN612.10-8-10-16-SW