



- 3 Type**
- MS** Brass pivot
 - KU** Plastic pivot (Polyacetal POM)
 - ZK** spherical pivot

d ₁	l ₁ Nominal length					d ₂ Brass pivot	d ₃ Plastic pivot	d ₄ Spherical pivot	l ₂ Brass pivot	l ₃ Plastic pivot	l ₄	l ₅ ≈ Spherical pivot	A/F
	16*	20	25	30	35								
M 6	16*	20	25	30	35	4	3,5	4,5 ±0,03	1	1,3	4	5,1	10
M 8	20*	25	30	35	45	6	5	6,1 ±0,05	1,5	1,6	5,3	6,2	13
M 10	25*	30	35	45	55	8	6,5	7,8 ±0,05	2	1,9	6,4	7,3	17

* only available in type MS and KU

Specification

- Hexagon head screw
Stainless Steel AISI 304 (A2)
- *Plastic characteristics* → Page 1141
- *Stainless Steel characteristics* → Page 1144
- **RoHS compliant**

Information

Stainless Steel-Hexagon head screws GN 933.5 with brass or plastic pivots are used when pressure dents or damage to the clamping surface must be avoided.

Stainless Steel-Hexagon head screws GN 933.5, type ZK, feature a spherical pivot whose diameter d₄ is smaller than the core diameter d₁ of the thread. This makes them suitable for holding thrust pads GN 631 / GN 631.5 which must be ordered separately.

see also...

- Grub screws GN 913.3 / GN 913.5 → Page 520 / 521

How to order

GN933.5-M6-20-KU

- | | |
|---|----------------|
| 1 | d ₁ |
| 2 | l ₁ |
| 3 | Type |